

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

1 Identification

- **Product identifier** EAEDC423
- **Trade name:** AIROMA-BERGAMOT BERGAMOT & SANDALWOOD
- **Manufacturer article number:** EAEDC423
- **Application of the substance / the mixture** Air freshener
- **Details of the supplier of the safety data sheet (913)(553)**
- **Manufacturer/Supplier:**
Vectair Systems Inc.
2095 Spicer Cove, Covington Way Distribution Centre, Memphis, TN 38134, USA
- +1 901 373 7818
- **Information department:** Product safety department prod-dev@vectairsystems.com
- **Emergency telephone number:**
- INFOTRAC +1 800 535 5053 INTERNATIONAL +1 352 323 3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Aerosols 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases under Pressure - Compressed gas H280 Contains gas under pressure; may explode if heated.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS04



GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Fragrance Trade Secret (913)

- **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 1)

· **Precautionary statements**

- P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
- P211 *Do not spray on an open flame or other ignition source.*
- P251 *Pressurized container: Do not pierce or burn, even after use.*
- P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*
- P264 *Wash thoroughly after handling.*
- P272 *Contaminated work clothing must not be allowed out of the workplace.*
- P280 *Wear protective gloves / eye protection / face protection.*
- P302+P352 *If on skin: Wash with plenty of water.*
- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P333+P313 *If skin irritation or rash occurs: Get medical advice/attention.*
- P321 *Specific treatment (see on this label).*
- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P363 *Wash contaminated clothing before reuse.*
- P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
- P411 *Store at temperatures not exceeding 48°C /120°F.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 4

Reactivity = 1

· **HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 4

Reactivity = 1

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	>50-≤100%
75-28-5	isobutane	>10-≤25%
74-98-6	propane	>2.5-≤10%
106-97-8	butane, pure	≤2.5%
	Fragrance Trade Secret (913)	≥1-≤2.5%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed** No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol-resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
 - **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
67-64-1	acetone	200 ppm
75-28-5	isobutane	5500* ppm
74-98-6	propane	5500* ppm
106-97-8	butane, pure	5500* ppm
120-51-4	Benzyl benzoate	5.7 mg/m ³
91-64-5	Coumarin	0.88 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	15 ppm
· PAC-2:		
67-64-1	acetone	3200* ppm
75-28-5	isobutane	17000** ppm
74-98-6	propane	17000** ppm
106-97-8	butane, pure	17000** ppm
120-51-4	Benzyl benzoate	63 mg/m ³
91-64-5	Coumarin	9.7 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	67 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 3)

· PAC-3:		
67-64-1	acetone	5700* ppm
75-28-5	isobutane	53000*** ppm
74-98-6	propane	33000*** ppm
106-97-8	butane, pure	53000*** ppm
120-51-4	Benzyl benzoate	380 mg/m ³
91-64-5	Coumarin	58 mg/m ³
5989-27-5	(R)-p-mentha-1,8-diene	170 ppm

7 Handling and storage

· Handling:

· **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

67-64-1 acetone	
PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 500 ppm
	Long-term value: 250 ppm
	A4, BEI
75-28-5 isobutane	
TLV	Short-term value: 1000 ppm
	(EX)
74-98-6 propane	
PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 4)

TLV	see Appendix F Minimal oxygen content (D, EX)
106-97-8 butane, pure	
REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: 1000 ppm (EX)
Ingredients with biological limit values:	
67-64-1 acetone	
BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Use suitable respiratory protective device in case of insufficient ventilation.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 5)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Aerosol

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

-44.5 °C (-48.1 °F)

· Flash point:

< 0 °C (< 32 °F)

· Flammability (solid, gaseous):

Not applicable.

· Auto igniting:

460 °C (860 °F)

· Decomposition temperature:

Not determined.

· Ignition temperature:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1.8 Vol %

· Upper:

13 Vol %

· Vapor pressure at 20 °C (68 °F):

3,000 hPa (2.300 mm Hg)

· Vapor pressure at 50 °C (122 °F):

800 hPa (600 mm Hg)

· Density:

Not determined.

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not applicable.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic:

Not determined.

· Solvent content:

· Organic solvents:

72.1 %

· VOC content:

25.99 %

259.9 g/l / 2.17 lb/gal

· Solids content:

0.0 %

· Other information

No further relevant information available.

US
(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

· Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· **IARC (International Agency for Research on Cancer)**

91-64-5	Coumarin	3
5989-27-5	(R)-p-mentha-1,8-diene	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD



(Contd. of page 7)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1950
· UN proper shipping name	
· DOT	Aerosols, flammable
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· DOT	
	
· Class	2.1 Gases
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases
· Label	2.1
· Packing group	
· DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Gases
· Hazard identification number (Kemler code): -	
· EMS Number:	F-D,S-U
· Stowage Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 8)

· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

67-64-1	acetone	ACTIVE
75-28-5	isobutane	ACTIVE
74-98-6	propane	ACTIVE
106-97-8	butane, pure	ACTIVE
25265-71-8	Dipropylene glycol (isomer unspecified)	ACTIVE
101-86-0	alpha-Hexylcinnamaldehyde	ACTIVE
51414-25-6	3-(4-Hydroxy-4-methylpentyl)cyclohex-3-ene-1-carbaldehyde	ACTIVE
106-22-9	dl-Citronellol	ACTIVE
120-51-4	Benzyl benzoate	ACTIVE
78-70-6	Linalool	ACTIVE
91-64-5	Coumarin	ACTIVE
5989-27-5	(R)-p-mentha-1,8-diene	ACTIVE
5392-40-5	Citral	ACTIVE
80-54-6	p-t-Butyl-alpha-methylhydrocinnamic aldehyde	ACTIVE
106-24-1	geraniol	ACTIVE

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/06/2024

Reviewed on 05/06/2024

Trade name: AIROMA-BERGAMOT BERGAMOT & SANDALWOOD

(Contd. of page 9)

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1 | acetone

I

· **TLV (Threshold Limit Value)**

67-64-1 | acetone

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product Safety Department

· **Contact:** +52 33 3688 0850

· **Date of preparation / last revision** 05/06/2024 / 6

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Aerosols 1: Aerosols – Category 1

Gases under Pressure - Compressed gas: Gases under pressure – Compressed gas

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

· * **Data compared to the previous version altered.**